



Lesonal Product Assortment

USEPA National Rule

Products	Mix Ratio	Hardener	Activator / Reducer	Applied VOC Less Water / Less Exempt
Pretreatment Wash Primer(s)		System Limit: 6.5 lbs/gal		Applied VOC Less Water / Less Exempt
Autoprep Etching Pen	Ready to use	N/A	N/A	0.0 lbs/gal
Self-Etching Primer CF	1:1	Self Etching Hardener CF	N/A	5.9 lbs/gal
Primer/Primer Surfacer		System Limit: 4.8 lbs/gal		Applied VOC Less Water / Less Exempt
Gray Urethane Surfacer	3:1:1	Urethane Surfacer Hardener	Lesonal Reducers, Extra slow, Slow, Medium, Fast, Extra Fast	3.8 lbs/gal
HS Surfacer/ Sealer	3:1:1	HS Surfacer/ Sealer Hardener	HS Surfacer Activator	4.5 lbs/gal
Epoxy Primer Sealer	2:1+10%	Epoxy Hardener Slow or Fast	Lesonal Reducers, Extra slow, Slow, Medium, Fast, Extra Fast	4.6 lbs/gal
Primer Sealer		System Limit: 4.6 lbs/gal		Applied VOC Less Water / Less Exempt
Gray Urethane Surfacer	2:1:20%	Urethane Surfacer Hardener	Lesonal Reducers, Extra slow, Slow, Medium, Fast, Extra Fast	3.9 lbs/gal
HS Surfacer/ Sealer	2:1:20%	HS Surfacer/ Sealer Hardener	Lesonal Reducers, Extra slow, Slow, Medium, Fast, Extra Fast	4.6 lbs/gal
<p>The VOC of the Multistage System (Basecoat/Mid-Coat/Clear) or (Foundation Coat/ Basecoat/ Clearcoat) System is found by composite calculations; The Basecoat/Clearcoat calculation is $VOC_{system} = (VOC_{bc} + 2VOC_{cc}) \div 3$ The Multistage calculation is $VOC_{system} = (VOC_{fc} + VOC_{bc} + 2VOC_{cc}) \div 4$</p>				
Multistage System (Basecoat)		System Limit: 5.0 lbs/gal		Applied VOC Less Water / Less Exempt
Lesonal SB	2:1	N/A	Lesonal Reducers, Extra slow, Slow, Medium, Fast, Extra Fast	6.6 lbs/gal
Lesonal WB	100:30	N/A	Lesonal Activator WB	3.4 lbs/gal
Multistage System (Clearcoat)		System Limit: 5.0 lbs/gal		Applied VOC Less Water / Less Exempt
Universal Clear	3:1:1	Clear Hardener	Clear Activator	4.2 lbs/gal
Glamour Clear	2:1:20%	Clear Hardener	Glamour Clear Reducer	4.0 lbs/gal
ProAir Clear	3:1	ProAir Clear Hardener (Fast or Slow)	N/A	3.9 lbs/gal
Mat Clear	3:1:1	Lesonal Clear Hardener	Lesonal Clear Activator, Slow or Fast	4.5 lbs/gal
Specialty Coatings (Adhesion Promoter)		System Limit: 7.0 lbs/gal		Applied VOC Less Water / Less Exempt
All Plastic Primer	Ready to Spray	N/A	N/A	6.9 lbs/gal
Lesonal Blending Additive	Ready to Spray	N/A	N/A	6.4 lbs/gal
1K Basefix	Ready to Spray 1:1	N/A	Lesonal Reducer Fast	6.2 lbs/gal 6.8 lbs/gal
Specialty Coatings (Uniform Finish Blender)		System Limit: 7.0 lbs/gal		Applied VOC Less Water / Less Exempt
Lesonal Blending Solvent	Ready to Spray	N/A	N/A	7.0 lbs/gal
Surfacer Cleaners		System Limit: Not Regulated		Applied VOC
Lesonal Surface Cleaner	N/A	N/A	N/A	6.3 lbs/gal
Lesonal Plastic Surface Cleaner	N/A	N/A	N/A	6.4 lbs/gal

